Speciation of arsenic in wastewater samples based on pyributicarbamate /ionic liquids by dispersive liquid-liquid microextraction

Nafiseh Esmacili^a, Nadia Kokabi^a, and Eskandar Kolvari^{a*}

^aDepartment of chemistry, Faculty of Science, Semnan University, Semnan, Iran

ARTICLE INFO:

Received 6 Dec 2019

Revised form 30 Jan 2020

Accepted 15 Feb 2020

Available online 28 Mar 2020

Keywords:

Arsenic, Speciation,
 Wastewater,
 Pyributicarbamate,
 Task specific Ionic liquid,
 Dispersive liquid-liquid
 microextraction

ABSTRACT

A simple and applied method based on O-3-Tert-butylphenyl N-(6-methoxy-2-pyridyl)-N-methylthiocarbamate (Pyributicarbamate; TBMPMTC) was used for arsenic speciation (As_{III} and As_V) in urine and water samples by dispersive liquid-liquid microextraction (DLLME) procedure. The concentrations of arsenic in the liquid phase were determined by hydride generation atomic absorption spectrometry in the presence of flame accessory (HG-AAS). By procedure, a mixture of ionic liquid (0.1 g, [APMIM][PF₆][HMIM][PF₆]), acetone (0.2 mL) and pyributicarbamate was injected into wastewater sample containing arsenic (As_{III} and As_V) ions, which were already extracted by pyributicarbamate at the optimized pH. The task-specific ionic liquid (TSIL) of 1-3-aminopropyl-3-methyl-imidazoliumhexafluorophosphate [APMIM][PF₆] was chemically synthesized and used for increasing of $As(V)$ extraction in the liquid phase. $As(III)$ was extracted based on the sulfur bond of pyributicarbamate at pH=5.3. $As(V)$ can be extracted by amine group of TBMPMTC and [APMIM][PF₆] at pH=3.0 ($As(V)---:NH_2$). The influence of parameters such as, pH, amount of ionic liquid, and ligand was studied. Based on results, the LOD, enhancement factor (EF) and linear range (LR) were obtained 3.2 ngL⁻¹, 9.85 and 0.01-1.2 µg L⁻¹, respectively. The procedure validated by certified reference material (CRM).

1. Introduction

The toxicities of heavy metals in waters cause to main problem in humans and environment and cannot be biodegraded as VOCs. The factories and chemical activity are real source of heavy metals such arsenic which can entrance to environment and caused different disease in humans such as, renal, liver and brain [1]. The most of arsenic in waters has two forms $As(III)$ and $As(V)$. The arsenic concentration in waters has generally ranged between 1 and 2 µg L⁻¹. Water in volcanic

rock and sulfide mineral has high levels about 12 mg L⁻¹. Mean arsenic concentrations in sediment the mean of As has ranges from 5 to 3000 mg kg⁻¹ [2, 3]. The occupational exposure and oral intake (food and water) of arsenic are the most important route in humans. The mean daily intake of arsenic from drinking water to human body must be less than 10 µg. By increasing of arsenic concentration in waters, dangerous diseases created in human body after drink waters for many times. Many changes in CNS and peripheral nervous system (PNS) such as, tenderness and vomiting headaches occurred for arsenic exposure. Liver and renal may moved to cancer problem as different toxicity and

* Corresponding author: Bahareh Fahimirad

Email: kolvari@semnan.ac.ir

<https://doi.org/10.24200/amecj.v3.i01.93>

oxidation state of arsenic [4-7]. Different analytical procedure used for arsenic determination of speciation/determination in water samples. A few of them only determination without speciation such as graphite furnace atomic absorption spectrometry (GF-AAS) [8], Flame atomic absorption spectrometry (F-AAS) [9], hydride generation atomic absorption spectrometry (HG-AAS) [10], capillary electrophoresis with inductively coupled plasma-mass spectrometry (CE-ICP)[11] and arsenic species can be determined with ion chromatography coupled to inductively coupled plasma mass spectrometry (IC-ICP-MS)[12]. As low concentration of arsenic species in waters (sub ppb), sample preparation must be used before instrumental analysis. Recently, solid-phase extraction (SPE) based on nanomaterials was used to improve the extraction procedure. For this purpose, many carbon structure such as, modified activated carbon [13], carbon nanotubes [14], and alumina supported on graphene oxide [15], were reported by researchers. In addition, the liquid-liquid extraction technique (LLE) and dispersive liquid-liquid microextraction (DLLME) was used for extraction analyte from liquid phase based on ligand by immiscible solvents or ionic liquid which was directly immersed in water samples and dispersed by acetone [16-22]. The organic solvents such as tetrachloride carbon are toxic. Therefore, the ionic liquids (ILs) as green solvents have used as extracting solvent. ILs has many advantages as compared to organic solvents, such as favorite vapor pressure, viscosity and density. Therefore, ILs have used as benign solvent in DLLME procedure.

In this study, a new procedure based on TBMPMTC -DLLME coupled to HG-AAS for the speciation and determination of trace amount of As (III) and As (V) in wastewater samples at pH of 5.3 and 3.0, respectively. Flame conditions with 1.2 Lmin⁻¹ fuel and minimum flow air have used.

2. Experimental

2.1. Apparatus

The experiments were performed using a GBC-932 atomic absorption spectrometer equipped with a

hydride generation module (HG3000-AAS -AUS). A hollow cathode lamp operated at a current of 8 mA and a wavelength of 193.7 nm with a spectral band width of 1 nm and deuterium background corrector was applied. The deuterium-lamp background corrector, As hollow-cathode lamp, and a circulating reaction loop was used for arsenic determination.

The instrument conditions of HG-AAS have showed in Table 1. The pH values of the solutions have adjusted by a digital pH meter (Metrohm 744, Herisau, Switzerland). A Hettich centrifuge (model EBA 20, Germany) and an ultrasonic bath with heating system (Tecno-GAZ SPA, Italy) have used.

Table 1. The instrumental parameters for analysis of arsenic

Features	Value
Precision (%RSD, N=10)	1.4
LOD	3.5 µg L ⁻¹
Linear range, PA	0.1 – 10.3 µg L ⁻¹
Wavelength	193.7 nm
Spectral band width	1 nm
Lamp current	8 mA
Correlation coefficient	R = 0.9997

PA = Peak Area, PH = Peak Height

2.2. Reagents and Materials

All the reagents were of analytical grade. Arsenic standard solutions were prepared from a stock solution of 1000 mg L⁻¹ as ultra trace in 2% nitric acid from Fluka Switzerland (CAS N: 39436). Arsenic (V) oxide prepared from Sigma, Germany (As₂O₅; CAS N: 1303-28-2). The powder of O-3-Tert-butylphenyl N-(6-methoxy-2-pyridyl)-N-methylthiocarbamate (pyributicarbamate; TBMPMTC) purchased from Sigma which was prepared daily by DW (C₁₈H₂₂N₂O₂S; CASN: 88678-67-5, Germany). 1-Hexyl-3-methylimidazolium hexafluorophosphate (C₁₀H₁₉F₆N₂P; CID 2734175; [HMIM][PF₆]) was purchased from Sigma, Germany. The ionic liquid of 1-(3-aminopropyl)-3-methyl-imidazoliumhexafluorophosphate [APMIM][PF₆] synthesis in center of organic chemistry in Semnan University, Iran. Sodium acetate /acetic as buffer solutions for pH 3–6 was

prepared from Sigma, Germany (1.5 mol L^{-1}). Ultrapure water has obtained from a water system of RIPI. The plastic, vials and glasses equipments were cleaned by soaking in HNO_3 (1 M) and were rinsed with deionized water for 10 times prior to use.

2.3. Sampling

Drinking and river water samples were collected paint and chemical wastewaters from Iran. These samples were immediately acidified with 0.1% of concentrated HCl which provided a pH lower than 2. The samples have then filtered in the laboratory using a pore membrane filter ($0.45 \mu\text{m}$, Macherey-Nagel, PTFE) to remove suspended solids.

2.4. Synthesis of [APMIM][PF6]

As reported by Hu and Yeon, the procedure of synthesis of [APMIM][PF6], was done by center of organic chemistry, Semnan. For this purposed methylimidazole and bromopropylammonium

bromide ($\text{C}_3\text{H}_9\text{Br}_2\text{N}$) dissolved in acetonitrile in boiling flasks with magnetic stirrer and refluxed at 90°C . Finally, the solution of [APMIM][Br] was obtained. After cooling, the KPF6 (10 g) added to 20 mL of DW) and after 24 h, the solvents were separated and the ionic liquid was removed by extraction in methanol/chloroform. The suspension was then filtered and washed with diethyl ether (10 times) to remove impurities [23, 24].

2.5. Procedure

After synthesis of [APMIM][PF6], the procedure followed by 0.5 mL of TBMPMTC solution (2%, w/w), 0.1 g of 1-Hexyl-3-methylimidazolium hexafluorophosphate in acetone solution (0.2 mL) which was mixed and injected to 10 mL of sample solution containing As(III)/As(V). The cloudy solution has shaken with a vortex for 5 min and pH adjusted up to 5.3 based on favorite buffer solutions. Then, the arsenic (III) was efficiently extracted ($\text{As}^{\cdot-}\text{SR}$) in [APMIM][PF6] @ [HMIM]

Speciation of arsenic in water samples based on pyributicarbamate by DLLME

Fig. 1. The procedure for speciation of arsenic in wastewater samples based on pyributicarbamate /ionic liquids

Arsenic Speciation based on Pyributicarbamate

Fig. 2. The mechanism of extraction of As(III) and As(V) based on TBMPMTC by DLLME procedure

[PF₆]. Finally, the IL separated in conical tube by centrifuging accessory for 7 min at 4000 rpm. The water sample removed from upper phase, arsenic (III) back extracted from IL with 0.25 mL of nitric acid solution (0.5M) in lower phase, dilution with DW up to 1 mL and determined by HG-AAS. As(V) was also extracted with same procedure in pH=3.0 by mixture of TBMPMTC/[APMIM][PF₆]. Total As was calculated by summarizing of As(III) and As(V) which was shown in Figure 1. In addition, the mechanism of proposed procedure has presented in Figure 2.

3. Results and Discussion

Analytical conditions for HG-AAS determination have optimized in this work. Absorption (S/N) and repeatability that were investigated for speciation and determination As(III) and As(V) in wastewater samples in paint factories and chemical industries by HG-AAS. In view of the possibility of As extraction with TBMPMTC, this ligand was used to chelated of arsenic in ionic liquids phase. All conditions such as pH, amount of IL, amount of TBMPMTC, sample volume and shaking time were optimized by DLLME procedure.

3.1 Effect of pH

The complexation phenomenon has strongly conditioned by the pH of solutions and subsequently

affects on the extraction efficiency of the As_{III}-SR and As_V-SR. For this reason, the pH between 2-10 was examined for As (III) and As(V) in water samples by DLLME method. Two groups of ligands include N and S bonding have important role in speciation arsenic in liquid phase when pH optimized. Based on solubility and charge of ions, they can be extracted by bonding group of TBMPMTC. The results showed, As (III) extracted with sulfur group of TBMPMTC at pH=4.8-5.5 and As (V) captured by amine group of TBMPMTC/[APMIM][PF₆] at pH=2.5-3.2. So, pH of 3.0 and 5.0 was selected as optimum pH in this study (Fig.3). The pH adjustments of samples were made using nitric acid (0.1 mol L⁻¹) for pH 1-2, and appropriate buffer solutions including sodium acetate (CH₃COONa/CH₃COOH, 1-2 mol L⁻¹) for pH 3.75-5.75, sodium phosphate (Na₂HPO₄/NaH₂PO₄, 0.2 mol L⁻¹) for pH of 5.8-8.0, and ammonium chloride (NH₃/NH₄Cl, 0.2 mol L⁻¹) for pH 8-10.

3.2. Effect of amount of TBMPMTC

It is important to establish the favorite concentration of ligand for arsenic extraction with high recovery as shown in Figure 4. The different concentration of TBMPMTC was used for optimization of arsenic extraction from 0.5 -50 micro molar. The results showed that the 17 micro molar has

Fig. 3. The effect of pH on arsenic speciation based on TBMPMTC by DLLME procedure

Fig. 4. The effect of amount of TBMPMTC on arsenic speciation by DLLME procedure

maximum recovery for arsenic (III, V) extraction from wastewater samples by DLLME. Based on statistical report in analytical chemistry the minimum ligand concentration was necessary to use with maximum extraction efficiency. So, the 20 micro molar selected as optimum concentration by proposed procedure.

3.3. Effect of amount of ionic liquid

The amount of ionic liquid as green organic solvent for extraction of arsenic in wastewaters must be optimized by DLLME. For this purpose, the different mass and kind of ionic liquid was studied. The results showed [HMIM][PF₆] have more extraction as compared to others ([BMIM][PF₆], [EMIM][PF₆], [MMIM][PF₆]). So, the 0.05-0.2 g of [HMIM][PF₆] examined by procedure. The quantitative extraction was observed for more than 0.08 g of [HMIM][PF₆] and therefore, 0.1 g

of [HMIM][PF₆] was chosen as optimum IL for further works (Fig. 5). The [APMIM][PF₆] had no effect on separation process but helped to increase efficiency extraction of As(V) from liquid phase.

3.4. Effect of sample volume and elution

The effect of sample volume was examined in a range of 1-20 mL for $\mu\text{g L}^{-1}$ As (III) and As(V). The quantitative extraction has observed less than 15 mL wastewaters. So, 10 mL of sample volume was selected in optimum conditions. The acid concentrations were used in order to obtain the maximum extraction with the minimal concentration and volume of the acid solution. The presented DLLME method based on the elution of arsenic species from IL phase with a mineral acidic solution achieved. Low pH leads to dissociation and releasing of As (III) and As(V) into the aqueous phase. So, 100-500 μL of different mineral

Fig. 5. The effect of amount of ionic liquid on arsenic speciation based on TBMPMTC by DLLME procedure

acids such as HCl, HNO₃, H₂SO₄ and H₃PO₄ (0.1-1 mol L⁻¹) were examined. The results showed that 0.5 mol L⁻¹ HNO₃ (250 µL) quantitatively back-extracted arsenic from IL.

3.5. Effect of dispersion time

Dispersion is the main factor in arsenic extraction by DLLME method and so, allows the direct contact of the analytes with TBMPMTC ligand and then extracted. Due to the dispersion of TBMPMTC/ILs into the aqueous phase, the mass-transfer phenomenon was obtained with high efficiency in short time. The influence of the shaking time was studied within the 1–5 min. The results showed that the relative response increased at 4 min and then remained constant. So, 5 min was chosen as favorite time as shaking. By centrifuging, the extraction was accelerated for phase separation between IL and liquid phase. The different times for centrifuging were tested from 2 to 10 min at 4000 rpm. The result showed that 5 min centrifugation time was sufficient to get a satisfactory biphasic system.

Table 2. The effect of interferences ions on extraction of As (III) and As (V) in water samples by DLLME procedure

Interfering Ions (M)	Mean ratio (C _M /C _{As(III)})	Recovery (%)
Ni ²⁺ , Co ²⁺ , Cd ²⁺	600	96.9
Mn ²⁺ , Cu ²⁺ , Zn ²⁺	900	98.7
I ⁻ , Br ⁻ , F ⁻ , Cl ⁻	1100	99.2
Na ⁺ , K ⁺ , Ca ²⁺ , Mg ²⁺	900	98.2
NO ₃ ⁻ , Cl ⁻ , F ⁻ , CO ₃ ²⁻	1200	97.4
Hg ²⁺	100	95.5
NH ₄ ⁺ , SO ₄ ²⁻	400	96.8
Pb ²⁺	250	97.3
Interfering Ions (M)	Mean ratio (C _M /C _{As(V)})	Recovery (%)
Ni ²⁺ , Co ²⁺ , Cd ²⁺	500	96.9
Mn ²⁺ , Cu ²⁺ , Zn ²⁺	800	98.7
I ⁻ , Br ⁻ , F ⁻ , Cl ⁻	900	99.2
Na ⁺ , K ⁺ , Ca ²⁺ , Mg ²⁺	900	98.2
NO ₃ ⁻ , Cl ⁻ , F ⁻ , CO ₃ ²⁻	1200	97.4
Hg ²⁺	200	95.5
NH ₄ ⁺ , SO ₄ ²⁻	500	96.8
Pb ²⁺	300	97.3

3.6. Interference of coexisting ions

As efficient analytical procedure in water samples, the interference of some coexisting ions was investigated in optimized condition. By DLLME procedure, the different concentration of the interfering ions added to 10 mL of standard sample solution containing 1.0 µg L⁻¹ of As (III) and As (V). The results showed that most of concomitant ions have no effect on the extraction efficiencies of As (III) and As (V) at the optimized pH. The tolerable concentration ratio of metals per As (III) and As (V) for Ni²⁺, Co²⁺, Cd²⁺, Mn²⁺, Cu²⁺, Zn²⁺, K⁺, Na⁺, Pb²⁺, Hg²⁺, NO₃⁻, Cl⁻, F⁻, CO₃²⁻ and SO₄²⁻ was obtained in water samples (Table 2).

3.7. Validation

The DLLME method based on TBMPMTC as a ligand was used for determination of As (III) and As (V) in 10 mL of wastewater and water samples by HG-AAS. The results were verified by spiking water samples with nickel standard solution. Based on results, the acceptable recovery was achieved by adding standard solution (As (III) and As (V) to real samples as a found analyte amount. The recoveries of spiked samples were 95-103% by DLLME methods (Table 3). Wastewaters of a chemical factory (A), a paint factory (B), well water (C), and drinking water (D) were selected as real samples which were used by procedure. The results demonstrated that TBMPMTC-DLLME can be used for speciation of As (III) and As (V) in wastewater, and water samples which were determined by HG-AAS. In addition, the certified reference material (CRM, NIST 2670) was used for validation As (III) and As (V) in urine samples by TBMPMTC-DLLME (Table 4).

4. Conclusions

The procedure has many advantages such as simplicity, reliability and high extraction efficiency in short time for arsenic speciation based on TBMPMTC-DLLME by sensitive HG-AAS technique. By improving the procedure, the favorite and acceptable preconcentration/separation/speciation of the trivalent and pentavalent inorganic

Table 3. Speciation and determination of As (III) and As (V) in spiked water samples by TBMPMTC-DLLME method

Sample	^a Added (μg L ⁻¹)		^a Found (μg L ⁻¹)		Total	Recovery (%)	
	As (III)	As (V)	As (III)	As (V)		As (III)	As (V)
A	-----	-----	0.432 ± 0.023	0.266 ± 0.014	0.698 ± 0.037	-----	-----
	0.4	-----	0.827 ± 0.043	0.262 ± 0.015	1.089 ± 0.052	98.8	-----
	-----	0.3	0.435 ± 0.022	0.568 ± 0.028	1.003 ± 0.049	-----	100.6
B	-----	-----	0.501 ± 0.023	0.197 ± 0.011	0.698 ± 0.034	-----	-----
	0.5	-----	0.993 ± 0.048	0.195 ± 0.009	1.188 ± 0.057	98.4	-----
	-----	0.3	0.498 ± 0.024	0.504 ± 0.026	1.002 ± 0.055	-----	102.3
C	-----	-----	0.102 ± 0.006	0.068 ± 0.003	0.170 ± 0.009	-----	-----
	0.1	-----	0.203 ± 0.009	0.064 ± 0.003	0.267 ± 0.012	101.0	-----
	-----	0.1	0.098 ± 0.005	0.165 ± 0.013	0.263 ± 0.018	-----	97
D	-----	-----	0.032 ± 0.001	ND	0.032 ± 0.001	-----	-----
	0.05	-----	0.081 ± 0.004	ND	0.081 ± 0.004	98	-----
	-----	0.05	0.030 ± 0.001	0.002 ± 0.048	0.078 ± 0.003	-----	96

^aMean of three determinations ± Confidence interval (P = 0.95)**Table 4.** Method validation for speciation of arsenic based on TBMPMTC-DLLME by standard reference material (ng L⁻¹)

sample	Certified value	Certified value	*Found	*Found	Recovery	Recovery
	As (III)	As (V)	As (III)	As (V)	As (III) (%)	As (V) (%)
CRM	833.3	500.0	827.4 ± 45.6	488.7 ± 24.6	99.3	97.7
Added	400.0	-----	1209.8 ± 58.5	482.3 ± 26.3	95.6	-----
Added	-----	500.0	831.2 ± 51.2	990.2 ± 47.7	-----	100.3

^aNIST CRM 2670, Arsenic in frozen dried urine, pH 4.0, - 20°C, diluted with DW(1:3)^bMean of three determinations ± confidence interval (P = 0.95)

forms of arsenic was achieved as alternative to HPLC-ICP-MS. The results showed the quantitative recovery more than 96% and EF of 9.85 as curve fitting analysis for As(III) /As(V) were obtained at pH of 5.0 and 3.0, respectively. If the ionic liquid of [APMIM][PF₆] as TSIL wasn't used, the recovery obtained up to 73% for As(V) in optimized conditions. The certified reference material and spiking real samples showed the high accuracy and precisions results which were agreement with the certified values. In DLLME procedures, the satisfactory results based on TBMPMTC ligand was achieved for arsenic species in wastewater samples.

5. References

- [1] R. Dixit, D. Malaviya, K. Pandiyan, U.B. Singh, A. Sahu, R. Shukla, B.P. Singh, J.P. Rai, P.K. Sharma, H. Lade, Bioremediation of heavy metals from soil and aquatic environment: an overview of principles and criteria of fundamental processes, *Sustainability*, 7 (2015) 2189-2212.
- [2] R. Nickson, J. McArthur, W. Burgess, K.M. Ahmed, P. Ravenscroft, M. Rahman, Arsenic poisoning of Bangladesh groundwater, *Nat.*, 395 (1998) 338-338.
- [3] M. Tuzen, K.O. Saygi, I. Karaman, M. Soylak, Selective speciation and determination of inorganic arsenic in water, food and biological samples, *Food Chem. Toxicol.*, 48 (2010) 41-46.
- [4] V.M. Nurchi, A.B. Djordjevic, G. Crisponi, J. Alexander, G. Björklund, J. Aaseth, Arsenic toxicity: Molecular targets and therapeutic agents, *Biomol.*, 10 (2020) 235.
- [5] M. Molin, S.M. Ulven, H.M. Meltzer, J. Alexander, Arsenic in the human food chain, biotransformation and toxicology—Review focusing on seafood arsenic, *J. Trace Elem. Med. Biol.*, 31 (2015) 249-259.
- [6] A. Emadi, S.D. Gore, Arsenic trioxide—an old drug rediscovered, *Blood Rev.*, 24 (2010) 191-199.
- [7] C.M. George, L. Sima, M. Arias, J. Mihalic, L.Z. Cabrera, D. Danz, W. Checkley, R.H.

- Gilman, Arsenic exposure in drinking water: an unrecognized health threat in Peru, *Bull. World Health Org.*, 92 (2014) 565-572.
- [8] A.Q. Shah, T.G. Kazi, J.A. Baig, M.B. Arain, H.I. Afridi, G.A. Kandhro, S.K. Wadhwa, N.F. Kolachi, Determination of inorganic arsenic species (As³⁺ and As⁵⁺) in muscle tissues of fish species by electrothermal atomic absorption spectrometry (ETAAS), *Food chem.*, 119 (2010) 840-844.
- [9] C. Zeng, Y. Yan, J. Tang, Y. Wu, S. Zhong, Speciation of Arsenic (III) and Arsenic (V) based on Triton X-100 hollow fiber liquid phase microextraction coupled with flame atomic absorption spectrometry, *Spect. Lett.*, 50 (2017) 220-226.
- [10] M. Welna, P. Pohl, Potential of the hydride generation technique coupled to inductively coupled plasma optical emission spectrometry for non-chromatographic As speciation, *J. Anal. Atomic Spect.*, 32 (2017) 1766-1779.
- [11] L. Liu, Z. Yun, B. He, G. Jiang, Efficient interface for online coupling of capillary electrophoresis with inductively coupled plasma-mass spectrometry and its application in simultaneous speciation analysis of arsenic and selenium, *Anal. Chem.*, 86 (2014) 8167-8175.
- [12] S.H. Son, W.B. Lee, D. Kim, Y. Lee, S.H. Nam, An alternative analytical method for determining arsenic species in rice by using ion chromatography and inductively coupled plasma-mass spectrometry, *Food Chem.*, 270 (2019) 353-358.
- [13] R. Sawana, Y. Somasundar, V.S. Iyer, B. Baruwati, Ceria modified activated carbon: an efficient arsenic removal adsorbent for drinking water purification, *Appl. Water Sci.*, 7 (2017) 1223-1230.
- [14] A. Naghizadeh, A.R. Yari, H.R. Tashauoei, M. Mahdavi, E. Derakhshani, R. Rahimi, P. Bahmani, H. Daraei, E. Ghahremani, Carbon nanotubes technology for removal of arsenic from water, *Arch. Hyg. Sci.*, 1 (2012) 6-11.
- [15] A. Baranik, A. Gagor, I. Queralt, E. Marguí, R. Sitko, B. Zawisza, Determination and speciation of ultratrace arsenic and chromium species using aluminium oxide supported on graphene oxide, *Talanta*, 185 (2018) 264-274.
- [16] J. Ali, M. Tuzen, T.G. Kazi, Determination of Total Arsenic in Water and Food Samples by Pressure-induced Ionic Liquid-based Dispersive Liquid-Liquid Microextraction Method Prior to Analysis by Hydride Generation Atomic Absorption Spectrometry, *Atomic Spect.*, 38 (2017) 57-64.
- [17] X. Wang, G. Xu, P. Chen, Y. Sun, X. Yao, Y. Lv, W. Guo, G. Wang, Fully-automated magnetic stirring-assisted lab-in-syringe dispersive liquid-liquid microextraction for the determination of arsenic species in rice samples, *RSC Adv.*, 8 (2018) 16858-16865.
- [18] E.F. Fiorentini, B.V. Canizo, R.G. Wuilloud, Determination of As in honey samples by magnetic ionic liquid-based dispersive liquid-liquid microextraction and electrothermal atomic absorption spectrometry, *Talanta*, 198 (2019) 146-153.
- [19] H. Shirkhanloo, M. Ghazaghi, M. Eskandari, Cloud point assisted dispersive ionic liquid-liquid microextraction for chromium speciation in human blood samples based on isopropyl 2-[(isopropoxycarbothioly) disulfanyl], *Anal. Chem. Res.*, 10 (2016) 18-27.
- [20] H. Shirkhanloo, A. Khaligh, H.Z. Mousavi, M. Eskandari, A.A. Miran-Beigi, Ultra-trace arsenic and mercury speciation and determination in blood samples by ionic liquid-based dispersive liquid-liquid microextraction combined with flow injection, *Chem. Papers*, 69 (2015) 779-790.
- [21] H. Shirkhanloo, Z.H. Mousavi, A. Rouhollahi, Preconcentration and determination of heavy metals in water, sediment and biological samples, *J. Serb. Chem. Soc.*, 76 (2011) 1583-1595.
- [22] H. Shirkhanloo, A.A.M. Beigi, M. Eskandari, B. Kalantari, Dispersive liquid-liquid microextraction based on task-specific ionic liquids for determination and speciation of chromium in human blood, *J. Anal. Chem.*, 70 (2015) 1448-1455.
- [23] Q. Hu, J. Zhao, F. Wang, F. Huo, H. Liu, Selective extraction of vanadium from chromium by pure [C8mim][PF6]: An anion exchange process, *Sep. Purif. Technol.*, 131 (2014) 94-101.
- [24] S.-H. Yeon, K.-S. Kim, S. Choi, H. Lee, H.S. Kim, H. Kim, Physical and electrochemical properties of 1-(2-hydroxyethyl)-3-methyl imidazolium and N-(2-hydroxyethyl)-N-methyl morpholinium ionic liquids, *Electrochim. Acta*, 50 (2005) 5399-5407.